HIKVISION[®]

DS-MH2311 Series Body Camera

Introduction

Body camera highly integrates with record, taping, capture, positioning, face recognition and comparison, etc. It can record the process and condition of events completely via record, taping, and capture. It satisfies the requirement of mobile duty and evidence record. It is widely applicable to public security protection, city management, industry and commerce, etc.



Key Feature

- 1080p HD recording.
- Max. 30 M (7296 × 4104) resolution of the captured picture.
- Transmits videos to central video platform via 4G wireless communication.
- Dual positioning modules of GPS and Beidou, uploading the location information to the center in real time.
- IR function to recognize the facial features in the captured picture even in dim environment.
- Waterproof and dustproof, applicable to all-day field work.
- 3G/4G/Wi-Fi network connection with flexible wireless transmission.
- Face detection, face picture capture, and upload.



Specification

Model		DS-MH2311/64G/GLE
Camera	Sensor Type	1/3" CMOS
	Min. Illumination	0.05 Lux
	FOV	Horizontal: 129° Vertical: 70° Diagonal: 140°
Screen	Dimension	2.4" TFT LCD
	Resolution	240 × 320
	Touchscreen	Supported
Image	Shutter	Digital shutter
	Day & Night	IR cut filter with auto switch (You can see human face within 3 m at night.)
Video	Stream Type	Main stream, sub-stream
	Main Stream Resolution	1080P/30 fps, 1280 × 720/30 fps, 720 × 480/30 fps
	Sub-Stream Resolution	1080P/30 fps, 1280 × 720/30 fps, 720 × 480/30 fps
	Sub-Stream Frame Rate	30 fps, 15 fps, 5 fps
	Video Compression	H.264, H.265
	Frame Rate Type	Constant frame rate, variable frame rate
	Video Resolution	1080P/30 fps, 1280 × 720/30 fps, 720 ×480 /30 fps
	Picture Resolution	5 M (3072 × 1728), 16 M (5312 × 2988), 30 M (7296 × 4104)
	Picture Format	JPEG
Audio	Audio Sampling Rate	16 kHz
	Audio Compression	G.711alaw, G.711ulaw, G.722.1, PCM
	Audio Compression Frame Rate	8K, 16K
Smart Function	Face Picture Capture	Face detection, face picture capture, and upload
Network Connection	Dial	Frequency band: LTE FDD: B1/B3/B5/B8 LTE TDD: B34/B38/B39/B40/B41 WCDMA: B1/B8
	Wi-Fi	802.11 b/g/n
	Wi-Fi Frequency Range	2.402 to 2.482 GHz
	Positioning	GPS, Beidou, GPS + Beidou
	Bluetooth	BT 4.2
	Interface Protocol	EHome 2.0, Hikvision SDK




General	CPU	8-core 64-bit processor
	Operating System	Android 9.0
	Memory	2 GB
	Encryption	AES 128 Bit
	Laser Positioning	Supported
	Indicator	Charging indicator, working indicator
	Button	On/off, capture, record, tape, SOS, PTT
	Weight	190 g (without should clip) (0.4 lb)
	Dimension (L × W × H)	95 × 60 × 29 mm (3.7 × 2.4 × 1.1 inch)
	Power Supply	Battery
	Working Temperature	-20 °C to 55 °C (-4 °F to 131 °F)
	Protection Level	IP67
	Drop Resistance	1.8m
	Working Humidity	≤ 90%
Light Supplement	IR	Supported
	White Light	Supported
Storage	Internal Storage Media	TF card
	Internal Storage Capacity	64 GB in standard, extendable up to 256 GB
Interface	Charging Interface	Mini USB 2.0
	МІС	Supported
	Speaker	Supported
	SIM Card Slot	MicroSIM
Battery	Dismountable Battery	Supported
	Battery Capacity	3,300 mAh
	Charging Time	≤ 4h

Note:

• The device can record about 13/15 hours continuously in 1080p/720p resolution when 4G, Wi-Fi, GPS, and LCD are disabled.



Typical Application



Dimension

