

## NP-SC6550 X-Ray Security Inspection System

NP-SC6550 X-Ray security inspection system is an advanced security detection system designed for briefcases, postal bags, express mails, hand held parcels, and small packages checking with a world leading x-ray screening and single-energy image processing technology.

With the popular tunnel size of 659mm (W) x 504 (H), compact and movable design, NP-SC6550 is an ideal economical security inspection solution for hotels, government agencies, transportation hubs, logistics industry, courts, prosecutors, prisons, embassies, factories, schools, hospitals, stadiums, exhibition halls, entertainment venues, etc.



### Key Features

- High performance with HD image, strong penetration, precise recognition
- Adopts embedded Linux operating system with multi-core ARM
- Energy saving and environment protection with low power consumption
- Supports real-time monitoring
- Supports multiple image processing mode
- Supports POST (power on self-test)
- 64X zoom in
- One-touch power off
- Energy-saving working mode for conveyor available
- Shock-proof design
- User friendly interface for easy operation

### System Functions

X-ray Image processing functions:

Color/Black & White, local enhancement, high penetration, low penetration, super enhancement, inverse color, light increase, light reduce, grey scale scan, image zoom in, edge enhancement.

System functions:


Power on self-diagnosis, multi levels user management, image management, TIP management, curve diagnosis, equipment information query, Multi-format image export, image mirroring, 1-16 times stepless zoom in, operator training, precise positioning of baggage images, clear channel reminder, one key calibration, one-key shutdown




## Specifications

| Model                                  | NP-SC6550   |
|--|---|
| Tunnel size                            | 659.4mm Wx504 mm H  |
| Conveyor height                        | 0.22 m/s  |
| Conveyor speed                         | 700mm   |
| Max. load                              | 150 kg (330.69 lb)  |
| Penetration (steel)                    | Standard 8 mm, 11mm by customize  |
| Wire resolution                        | 40AWG   |
| Spatial resolution                     | Vertical: 1.0 mm<br>Horizontal: 1.0 mm  |
| X-ray dose per inspection              | < 3.5 $\mu$ Sv  |
| X-ray leakage                          | < 1 $\mu$ Sv/h  |
| X-ray generator                        | Anode Voltage: 80 kV, 100% Oil Cooling,<br>Single generator, vertical beam direction. |
| Images colors                          | B/W, Colors   |
| Images storage                         | 10000 images  |
| Film safety                            | ISO1600   |
| Working temperature                    | 5 °C to 40 ° C (41 °F to 104 °F)  |
| Working humidity                       | 0% to 90%   |
| Operation system                       | Linux   |
| Power supply                           | AC 220 V (+ 10% to -15%), 50 Hz ( $\pm$ 3 Hz)   |
| Power consumption                      | 0.8 kw  |
| Dimension (L x W x H)<br>without table | 2195mm x 902 mm x 1362.5 mm (86.42" x 35.51" x 53.64")                                |
| Weight                                 | 420 kg (925.94lb)   |
| Extended table                         | 614mm   |
| Accessories                            |   |
| Extended table                         | 614mm x1 in exit ( Included )   |
| LCD monitor                            | 17" LCD Color Monitor x1 included   |
| Dedicated Key board &mouse             | Standard included   |

## Dimension




## Scanned Images



## Available Model

NP-SC6550

Distributed by



**HIKVISION®**

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahirvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 (216)521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com